



- AL+MY:4*(8+11)al/my/my
- insulation:7pairs,FPE,OD: Ø0.90±0.02
- conductor:7Cx[30AWG(7/0.25Cu)x1 pair]
- DRAIN:4Cx30AWG(0.25Cu)
- conductor:5Cx30AWG(0.25Cu)
- insulation:5core,OD: Ø0.65±0.03, HDPE(1 twisted)
- AL/MY:AL/MY,0.025*22mm
- DRAIN**:16/6/0.12AL
- jacket:Ø7.3±0.15mm
- UL PVC,70P,black

30AWG(7P+5C)

- FE-DD-6IN 150MM(6IN)+/-20MM
- FE-DD-01 450MM(1.5FT)+/-20MM
- FE-DD-03 905MM(3FT)+/-30MM
- FE-DD-06 1830MM(6FT)+/-30MM
- FE-DD-10 3050MM(10FT)+/-50MM
- FE-DD-15 4570MM(15FT)+/-50MM

DVI-D	Signal Assignment	DVI-D
2		2
1		1
3		3
5		5
4		4
10		10
9		9
11		11
13		13
12		12
18		18
17		17
19		19
21		21
20		20
22		22
23		23
24		24
6		6
7		7
15		15
14		14
16		16
SHELL		SHELL

2		DVI-SHELL	2PCS	
1		DVI 24+1 GOLD PLUG	2SET	
NO.	DRAW	SPEC	QTY	
DES.		MTL.		MDL.
CHK.		TRL.		PDT
APPR.		QTY	VER	SCL
MY CABLEMART LLC		A-1		Title.
Unit: MM		Page 1	Pages 1	Drw. NO.

DVI-D-DVI-D CABLE

30AWG